

ULTI-USE M

NO MORE PUMPING!

IRI

NEXT GENERATION, HIGHER PERFORMANCE MOTOR & PUMP delivers 36% more output than earlier design to handle a wider range of chemical applications.

CONSISTENT CHEMICAL SPRAY OUTPUT ensures optimal application rates saving time and reducing chemical waste.

WITH A NEW NOZZLE ASSORTMENT, THIS SPRAYER WILL NOW SPRAY UP TO 35' using the special streaming nozzle and will handle higher viscosity chemicals with the included brown fan nozzle.

IMPROVED, THICKER WALLED HOSE reduces kinking and offers a longer service life.

UNIQUE STEEL SLEEVE/POLY WAND composite construction is 3X stronger than most metal wand designs while offering broader chemical compatibilities.

TANK AND SHUTOFF FILTERS are tool free for service and ensure clog free performance for liquid and wettable powder chemicals.

VITON® and SANTOPRENE SEALS offer broad chemical compatibilities for agronomic janitorial, pest control, degreasing and construction maintenance chemicals.

ERGONOMIC, DELUXE HARNESS with IMPROVED UV RESISTANT CONSTRUCTION offers incredible day long comfort and better durability to stand up to the elements.



LITHIUM-ION BACKPACK SPRAYER

SDDAV DISTANCE

APPLICATIONS FROM A DISTANCE

ITON EALS

CHEMICALLY RESISTANT TO SWELLING AND HIGH TEMPERATURES

C

SPRAYS UP TO **4 hrs.** PER CHARGE

CHADGE





CHEMICALLY **COMPATIBLE WITH:**

for **FINE MISTING**

APPLICATIONS

- BLEACH (Up to 7% Dilution.
- Not for use with brass nozzle) Chlorhexidine
- Calcium Oxide (quicklime)
- Hydrogen Peroxide and other Peroxides
- Hypochlorous Acid
- Iodine Compounds
- Phenol
- Quaternary Ammonium ("quats", QAC)

190676


- Sodium Chloride
- Thymol, or Thymox[®]











I

| Tank Capacity | 4 Gallons | |
|-----------------|----------------------|--|
| Extension | 21" Stainless Steel | |
| Hose Length | 50" Nylon Reinforced | |
| UPC | 8 41688 00567 9 | |
| Pallet Quantity | 24 | |

Performance

| Flow Rate | 0.3 GPM at 40 PSI |
|---------------------------|-------------------|
| Spray Distance | UP TO 34 FEET |
| Spray Duration Per Charge | UP TO 4 HOURS |
| Spray Volume Per Charge | 50 GALLONS |

Replacement Parts

| 18V, 4.0 Ah Li-ion Battery Pack | No. 183613 |
|---------------------------------|------------|
| 18V, 2.0 Ah Li-ion Battery Pack | No. 183612 |
| 18V Li-ion Charger, Fast | No. 183614 |
| 18V Li-ion Charger, Standard | No. 183615 |
| 18V Li-ion Charger, Vehicle | No. 183832 |
| Sanitizing Optimizer Kit | No .184828 |
| Warranty | 1 Year |

NOTES: Always follow chemical manufacturers' directions for proper use. Sodium hydroxide (lye, caustic soda, soda ash) are not recommend for use with any sprayer. These are highly corrosive to some of the materials and when mixed with water can produce a violent reaction. Some formulas may cause irritation of the skin and lungs. It is recommended that appropriate PPE is always worn while spraying disinfectants and sanitizers. Always follow the safety and use recommendations on the label. Many disinfectants and sanitizers are flammable. Never spray near heat sources and store in low temperature environments. Follow the label recommendations.





23 Garden Street, New York Mills, NY 13417 office: 315.736.0037 www.TheFountainheadGroup.com

Also Accepts TeeJet® Nozzles

FOAMING

MAX VOLUME FAN (BROWN) HIGH VOLUME FAN (RED) LOW VOLUME FAN (YELLOW)

ADJUSTABLE BRASS JET STREAM