



User-controlled VARIABLE FLOW from 0.1 to 0.6 GPM

FLOIQ™ VARIABLE FLOW TECHNOLOGY

Patented technology provides customized performance per application.

VARIABLE FLOW from 0.1 - 0.6 GPM ~ 90PSI MAX

- · Adjust flow rate for a broad range of applications & uses.
- Eliminates over-application of product.
- Consistent application rate increases efficiency on the job!

18V 2.0AH LI-ION BATTERY POWERED

Provides consistent pressure, saves time and energy!

SEALED and WATER RESISTANT BATTERY COMPARTMENT and SHROUD

for internal protection from the elements.

DELUXE HARNESS with PADDED WAIST BELT provides all day comfort.

50" HEAVY-DUTY KINK-RESISTANT HOSE No Kinking/No Damage.

PROFESSIONAL SHUT-OFF with COMFORT GRIP, LOCK & FILTER

can be easily operated with all required PPE.

POLY-LINED STAINLESS STEEL WAND

is stronger and more durable than brass.

VITON® SEALS resist harsh chemicals.



18V / 2.0Ah LITHIUM-ION **BATTERY** and 110V FAST **CHARGER** (Included)



ERGONOMICALLY DESIGNED FOR THE HARSHEST WORK **ENVIRONMENTS.**

SMITH

18 POWER



INTELLIGENT PRESSURE SWITCH

Internal pressure switch automatical**l**y toggles between high and low to manage peak pressure at the low (1-3) and high (4-10) settings.



INTELLIGENT FLOW MONITORING

Automatically adjusts to maintain consistent output pressure and flow for any dial setting regardless of battery life.



VARIABLE FLOW BACKPACK SPRAYER

www.smithperformancesprayers.com/pest-control

18 POWER



LITHIUM-ION POWERED

VARIABLE FLOW BACKPACK SPRAYER

HEAVY-DUTY KINK-RESISTANT

PROFESSIONAL SHUT-OFF with COMFORT GRIP, **LOCK & FILTER**

WIDE 4.75" FILLING CAP

NOZZLE STORAGE CLIP

CONVENIENT VERTICAL WAND STORAGE

21" POLY-LINED STAINLESS STEEL WAND STRONGER AND MORE **DURABLE THAN BRASS**

DELUXE HARNESS WITH REMOVABLE WAIST BELT







PEST CONTROL



CONSTRUCTION

CUSTODIAL

Specifications		
Empty Weight	16 Lbs	
Tank Capacity	4 Gallons	
Wand	21" Poly-Lined SS	
Hose Length	50" Kink-Resistant 7 Included	
Quick Change Tips		
Pallet Quantity	20	

Compatible with Popular Formulations

Flow Rate	0.1 TO 0.6 GPM	
Pressure Range	2 TO 90 PSI	
Spray Distance	UP TO 34 FEET	
Spray Height	UP TO 35 FEET	
pray Duration Per Charge UP TO 4 HOU		
Spray Volume Per Charge	50 GALLONS	

Optional Accessories

18V Li-ion Battery Pack, 2.0 Ah	No. 183612
18V Li-ion Battery Pack, 4.0 Ah	No. 183613
18V Li-ion Fast Charger, 110V input	No. 183614
18V Li-ion Compact Charger, 12V input	No. 183615
18V Li-ion Vehicle Charger, 12V input	No. 183831



CAP WAND GROOVE FOR TIGHTENING & LOOSENING



LED BATTERY LIFE INDICATOR



NOZZLE STORAGE CLIP







ADJUSTABLE BRASS Adjusts from solid

JET STREAM Pinpoint stream stream to fine mist. for targeted applications from a distance.

7 SPRAYING NOZZLES



FOAMING Creates a lite

foam to improve weed killing performance and track where you spray.



HIGH VOLUME

WIDE FAN

higher viscosity





WIDE FAN Flat spray for very Flat spray broad coverage and for broader coverage.



Flat spray

spraying.

for precision

LOW VOLUME NARROW FAN (Yellow)

HIGH VOLUME FOAMING Broad foam coverage for horizontal and vertical surfaces.













